

기술 자료

# Fluke 27 II Rugged Digital Multimeter



## 주요 기능

- Measure up to 1000 V AC and DC
- Measure up to 10 A (20 A for 30 seconds)
- 10,000  $\mu$ F capacitance range
- Frequency to 200 kHz
- Extended AC voltage bandwidth – 40 Hz to 30 kHz
- Resistance, continuity and diode test
- Min/Max and average recording to capture variations automatically

## 제품 개요: Fluke 27 II Rugged Digital Multimeter

### The standard for rugged

The Fluke 27 II Digital Multimeter define a the standard for operating in harsh conditions with the features and accuracy to troubleshoot most electrical problems. Both meters have IP 67 (waterproof and dustproof) rating, MSHA approvals, extended operating temperature range of -15 °C to +55 °C (5 °F to 131 °F, -40 °C for up to 20 minutes) and 95% humidity, and have been designed and tested to withstand a 3 m (10 ft) drop. The Fluke 20 Series Multimeters are built to work in the toughest environments.

## 제품 사양: Fluke 27 II Rugged Digital Multimeter

| Accuracy Specifications |                               |                                              |
|-------------------------|-------------------------------|----------------------------------------------|
| DC voltage              | Range                         | 0.1 mV to 1000 V                             |
|                         | Accuracy                      | 0.1% + 1                                     |
| AC voltage              | Range                         | 0.1 mV to 1000 V                             |
|                         | Accuracy                      | 0.5% + 3                                     |
| DC current              | Range                         | 0.1 μA to 10 A                               |
|                         | Accuracy                      | 0.2% + 4                                     |
| AC current              | Range                         | 0.1 μA to 10 A                               |
|                         | Accuracy                      | 1.5% + 2                                     |
| Resistance              | Range                         | 0.1 Ω to 50 MΩ                               |
| Display counts          | 6000                          |                                              |
| Capacitance             | 1 nF to 9999 μF               |                                              |
| Frequency               | 0.5 Hz to 199.99 kHz          |                                              |
| Compliance              | CAT IV 600 V , CAT III 1000V  |                                              |
| IP rating               | IP 67                         |                                              |
| Power                   | Three AA batteries            |                                              |
| Battery life            | 800 hours                     |                                              |
| General Specifications  |                               |                                              |
| Display                 | Bar graph/backlight           | Yes/Yes                                      |
| Data storage            | Min/Max/Avg                   | Yes                                          |
|                         | Reading hold                  | Yes                                          |
| Other features          | Relative readings (zero)      | Yes                                          |
|                         | Battery type                  | Three AA batteries                           |
| Warranty and protection | Safety rating                 | CAT IV 600 V/CAT III 1000 V                  |
|                         | Mine safety                   | MSHA Approved                                |
|                         | External protection           | Rubber holster                               |
|                         | Drop test                     | 10 feet drop test                            |
|                         | Dustproof/waterproof          | Yes, IP 67 rated                             |
|                         | Warranty                      | Limited lifetime                             |
|                         | Size (H x W x L) with holster | 6.35 x 10.0 x 19.81 cm (2.5 x 3.93 x 7.8 in) |
| Weight with holster     | 698.5 g (1.54 lb)             |                                              |

## 모델



### FLUKE 27-II

산업용 멀티미터

Includes:

- Holster
- Test Leads
- Alligator Clips
- Printed getting started manual
- CD ROM manual
- 3 AA batteries

**Fluke. *Keeping your world up and running.***<sup>®</sup>

Fluke Corporation  
PO Box 9090, Everett, WA 98206 U.S.A.

(주)한국플루크Fluke Korea  
Tel.02.539.6311  
(주)한국플루크 대구지사  
Tel.053.382.6311  
[www.fluke.co.kr](http://www.fluke.co.kr)

Fluke Korea  
서울특별시 강남구 영동대로 517,10층 1002호  
(삼성동, 아셈타워)

©2023 Fluke Corporation.  
사양은 예고 없이 변경될 수 있습니다.  
02/2023

이 문서의 수정은 Fluke Corporation 의 서면 허가 없이는 허용되지 않습니다.